



Evolve™ E10 2.0

Enhance the shopper experience

Checkpoint® 

*Intelligent Retail
Solutions*

Evolve

E10 2.0

Enhance the shopper experience

Retailers continue to seek solutions that combine both inventory control and loss prevention to optimize operations and customer experience whilst complimenting the stores' aesthetics.

Designed to be flexible around the dynamic needs of the retail industry, the E10 2.0 offers practical migration of EAS and RFID. With a diverse range of design options, plus integrated visitor counting and connection to Checkpoint's data analytic app - EVOLVE-Store™, the E10 delivers an attractive, data centric solution for complete visibility of your stores.

With almost infinite design options thanks to the easily accesible ad panels, the E10 allows for retailers to create an antenna which blends with store aesthetics and branding, accommodating both printed paper formats or high impact fabric covers in any design/message, ensuring that store entrances are inviting and engaging for potential customers.

Available as RF only, RF/RFID dual technology and RFID only, the E10 2.0 protects your investment by supporting the migration from traditional EAS to RFID as and when you are ready.

RF AND/OR RFID TECHNOLOGY

flexible adoption of RFID technology

ALMOST INFINITE DESIGN OPTIONS

for your store requirements

INTEGRATED VISITOR COUNTING

enables shopper traffic analysis

EVOLVE-STORE READY

data analytics and store compliance monitoring

ORC JAMMER DETECTION

detects illegal jammer devices



EVOLVE E10 2.0

- DUAL RF & RFID technology
- Wirama Radar™ (ask for more details)
- TCP/IP network connectivity
- Visiplus overhead counter integration
- Integrated visitor counting
- Data reporting services available
- Remote service capability
- Advertising options available: paper inserts & printed fabric

DIMENSIONS

Height: 1.5 Meters / 4 feet 11 inches
Width: 0.45 Meters / 1 feet 5 inches
Body depth: 0.05 Meters / 6 feet 1 / 4 inches
Foot depth: 0.16 Meters / 2 inches

PART NUMBERS

Please speak to your regional account manager

FREQUENCY

ETSI 865.6 - 867.6 MHz
FCC/IC 902 - 928 MHz
7.2 - 9.5 MHz - NA
8.2 MHz - EU

PROTOCOL

ISO 18000-6C
(EPC Class 1 gen 2)